

THE SHOWDOWN

MOHAWK VS. THE COMPETITION - 44 OZ COMMERCIAL HOBNAIL

WEAR RESISTANCE

ASTM Tabor Test showing number of cycles of abrasion until backing is evident.



SOIL REMOVAL

ASTM Soil Test showing composite score of soil removed on AATC scale of 1 to 400.



MOISTURE REMOVAL

AATC Test Method for Moisture removal. A higher number indicates greater efficacy.



GREASE REMOVAL

Nissan Standard shoe rub was used to show amount of grease removed from shoe.



STYLE: CASCABEL CT

PRODUCT SPECIFICATION COMPARISON

MOHAWK

Fiber: 100% PET Polyester Fully Recycled from Post-consumer Drinking Bottles. Solution Dyed

Weight: 44 ounces per SY

Thickness: .370 inches

Pile Height: 4.0 mm

VOC Emissions: CAL 1350 (ASTM D5166) Meets all requirements.

Flammability: Pill Test DOC (FF 1-70) - PASS

Critical Radiant Flux: NFPA 101 Classification CLASS 1

Optical Smoke Density: ASTM (E662-13d) - PASS

Country of Origin: MADE IN THE USA

THE COMPETITION

Fiber: 100% Polypropylene No Recycled Content Solution Dyed

Weight: 44 ounces per SY

Thickness: .375 inches

Pile Height: 3.175 mm

VOC Emissions: CAL 1350 (ASTM D5166) Meets all requirements.

Flammability: Pill Test DOC (FF 1-70) - PASS

Critical Radiant Flux: NFPA 101 Classification CLASS 2

Optical Smoke Density: ASTM (E662-13d) - PASS

Country of Origin: IMPORTED