

THE SHOWDOWN

MOHAWK VS. THE COMPETITION - 44 OZ COMMERCIAL HOBNAIL

**WEAR RESISTANCE**

ASTM Tabor Test showing number of cycles of abrasion until backing is evident.



**SOIL REMOVAL**

ASTM Soil Test showing composite score of soil removed on AATC scale of 1 to 400.



**MOISTURE REMOVAL**

AATC Test Method for Moisture removal. A higher number indicates greater efficacy.



**GREASE REMOVAL**

Nissan Standard shoe rub was used to show amount of grease removed from shoe.



**STYLE: CASCABEL CT**

**PRODUCT SPECIFICATION COMPARISON**

**MOHAWK**

Fiber: 100% Polyester  
 Weight: 44 ounces per SY  
 Thickness: .370 inches  
 Pile Height: 4.0 mm  
 VOC Emissions: CAL 1350 (ASTM D5166)  
 Meets all requirements.  
 Flammability: Pill Test DOC (FF 1-70) - PASS  
 Critical Radiant Flux: NFPA 101 Classification  
 CLASS 1  
 Optical Smoke Density: ASTM (E662-13d) - PASS  
 Country of Origin: Made in the USA with US and imported fibers

**THE COMPETITION**

Fiber: 100% Polypropylene  
 No Recycled Content  
 Solution Dyed  
 Weight: 44 ounces per SY  
 Thickness: .375 inches  
 Pile Height: 3.175 mm  
 VOC Emissions: CAL 1350 (ASTM D5166)  
 Meets all requirements.  
 Flammability: Pill Test DOC (FF 1-70) - PASS  
 Critical Radiant Flux: NFPA 101 Classification  
 CLASS 2  
 Optical Smoke Density: ASTM (E662-13d) - PASS  
 Country of Origin: IMPORTED